

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/541,311	01/24/2006	Brigitte Bandl-Konrad	095309.56500US	8148	
23911 7	7590 07/10/2006		EXAMINER		
CROWELL & MORING LLP INTELLECTUAL PROPERTY GROUP			TRAN, BINH Q		
P.O. BOX 143		.	ART UNIT	PAPER NUMBER	
WASHINGTO	ON, DC 20044-4300		3748		
			DATE MAILED: 07/10/2006	DATE MAILED: 07/10/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

·		•	E
	Application No.	Applicant(s)	
	10/541,311	BANDL-KONRAD ET AL.	
Office Action Summary	Examiner	Art Unit	
	BINH Q. TRAN	3748	
The MAILING DATE of this communication Period for Reply	appears on the cover sheet w	vith the correspondence address -	•
A SHORTENED STATUTORY PERIOD FOR RE WHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CFF after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory per - Failure to reply within the set or extended period for reply will, by state Any reply received by the Office later than three months after the meanned patent term adjustment. See 37 CFR 1.704(b).	B DATE OF THIS COMMUNICATION OF THIS COMMUNI	ICATION. reply be timely filed NTHS from the mailing date of this communicated (35 U.S.C. § 133).	·
Status			
1) Responsive to communication(s) filed on _			
2a) ☐ This action is FINAL . 2b) ☑ T	his action is non-final.		
3) Since this application is in condition for allo	wance except for formal mat	iters, prosecution as to the merits	s is
closed in accordance with the practice unde	er <i>Ex par</i> te Quayle, 1935 C.I	D. 11, 453 O.G. 213.	
Disposition of Claims		·	
4) Claim(s) 16-44 is/are pending in the applica	ation.		
4a) Of the above claim(s) is/are without	drawn from consideration.		
5) Claim(s) is/are allowed.	•		
6)⊠ Claim(s) <u>16-44</u> is/are rejected.			,
7) Claim(s) is/are objected to.			
8) Claim(s) are subject to restriction an	d/or election requirement.		
Application Papers			
9) The specification is objected to by the Exam	niner.		
10) The drawing(s) filed on is/are: a) a	accepted or b) objected to	by the Examiner.	
Applicant may not request that any objection to	the drawing(s) be held in abeya	ince. See 37 CFR 1.85(a).	
Replacement drawing sheet(s) including the cor 11) The oath or declaration is objected to by the		•	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for fore a) All b) Some * c) None of:	ign priority under 35 U.S.C.	§ 119(a)-(d) or (f).	
1. Certified copies of the priority document	ents have been received.		
2. Certified copies of the priority docum	ents have been received in /	Application No	
Copies of the certified copies of the p	priority documents have been	n received in this National Stage	
application from the International Bur			
* See the attached detailed Office action for a	list of the certified copies no	t received.	
Attachment(s)			
1) Notice of References Cited (PTO-892)	4) 🗍 Interview	Summary (PTO-413)	
2) D Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No	(s)/Mail Date Informal Patent Application (PTO-152)	
 Information Disclosure Statement(s) (PTO-1449 or PTO/SB, Paper No(s)/Mail Date <u>01/24/2006</u>. 	6) Other:		

DETAILED ACTION

Receipt and entry of Applicant's Preliminary Amendment dated July 05, 2005 is acknowledged.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 16-32, and 33-40 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. More specifically,

- In claim 16, line 6, the phase "capable of " is indefinite. The phase has been held that the recitation that an element is "capable of " performing a function is not a positive limitation but only requires the ability to so perform. It does not constitute a limitation in any patentable sense. In re Hutchison, 69 USPQ 138.
- In claim 16, lines 7 and 10, the use of alternative expression "at least one of at one of "
 renders the claims indefinite.
- In claim 33, lines 10-11, the use of alternative expression "and/or" renders the claims indefinite because the expressions on either side of the "and/or" are not considered equivalent and cause uncertainty with respect to the scope of the claims.

The claims not specifically mentioned are indefinite since they depended from one of the above claims.

Application/Control Number: 10/541,311

Art Unit: 3748

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- (e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

The changes made to 35 U.S.C. 102(e) by the American Inventors Protection Act of 1999 (AIPA) and the Intellectual Property and High Technology Technical Amendments Act of 2002 do not apply when the reference is a U.S. patent resulting directly or indirectly from an international application filed before November 29, 2000. Therefore, the prior art date of the reference is determined under 35 U.S.C. 102(e) prior to the amendment by the AIPA (pre-AIPA 35 U.S.C. 102(e)).

Claims 16-17, 19-21, and 23-44 are rejected under 35 U.S.C. 102 (e) as being anticipated by Twigg et al. (Twigg'874) (Patent Number 6,863,874).

Regarding claims 16-17, 19-21, 23, 33, and 41, Twigg'874 discloses an installation for aftertreatment of exhaust gas (100) generated by an internal combustion engine (See col. 5, lines 5-15), comprising: a nitrogen oxide storage catalytic converter (28), an SCR catalytic converter (30) arranged either downstream of or integrated with the nitrogen oxide storage catalytic converter, said SCR catalytic converter being capable of storing ammonia, and at least one of: an

Application/Control Number: 10/541,311

Art Unit: 3748

NO2 producing catalytic converter arranged upstream of the SCR catalytic converter, and a particulate filter (16) arranged at one of: (i) a position upstream of the nitrogen oxide storage catalytic converter; an oxidation catalytic converter (14) arranged as a first exhaust gas aftertreatment component, as seen in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claims 24-25, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 26, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 27, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 28, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic .

Application/Control Number: 10/541,311

Art Unit: 3748

converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 29, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 30, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 31, Twigg'874 further discloses that the nitrogen oxide storage catalytic converter and the SCR catalytic converter are integrated in a common, combined catalytic converter which includes a nitrogen oxide storage catalyst material and an SCR catalyst material in mixed form or alternating in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 32, Twigg'874 further discloses that the engine is a motor vehicle propelling engine (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 34, Twigg'874 further discloses that wherein a desired ammonia generation quantity which is to be generated during a current regeneration operating phase of the

Application/Control Number: 10/541,311 Page 6

Art Unit: 3748

nitrogen oxide storage catalytic converter is determined, and the subsequent regeneration operating phase is carried out as a function of the desired ammonia generation quantity determined (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claims 35 and 42, Twigg'874 further discloses that wherein a condition whereby the recorded exhaust gas air ratio downstream of the nitrogen oxide storage catalytic converter drops below a threshold value, which is predetermined as a function of the desired ammonia generation quantity, is used as a criterion for terminating a respective regeneration operating phase of the nitrogen oxide storage catalytic converter (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 36, Twigg'874 further discloses that wherein a condition whereby the recorded exhaust gas air ratio downstream of the nitrogen oxide storage catalytic converter drops below a threshold value, which is predetermined as a function of the desired ammonia generation quantity, is used as a criterion for terminating a respective regeneration operating phase of the nitrogen oxide storage catalytic converter (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claims 37 and 43, Twigg'874 further discloses that wherein during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Application/Control Number: 10/541,311 Page 7

Art Unit: 3748

Regarding claims 38 and 44, Twigg'874 further discloses that wherein during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 39, Twigg'874 further discloses that wherein, during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Regarding claim 40, Twigg'874 further discloses that wherein, during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 5, lines 4-67; col. 6, lines 1-7; col. 7, lines 1-25).

Claims 16, and 32-44 are rejected under 35 U.S.C. 102 (e) as being anticipated by Stanglmaier et al. (Stanglmaier) (Patent Number 6,732,507).

Regarding claims 16, 33, and 41, Stanglmaier discloses an installation and method for aftertreatment of exhaust gas (14) generated by an internal combustion engine (10), comprising: a nitrogen oxide storage catalytic converter (20), an SCR catalytic converter (30) arranged either downstream of or integrated with the nitrogen oxide storage catalytic converter, said SCR catalytic converter being capable of storing ammonia, and at least one of: an NO2 producing catalytic converter arranged upstream of the SCR catalytic converter, and a particulate filter (40) arranged at one of: (i) a position upstream of the nitrogen oxide storage catalytic converter; (ii) a position between the nitrogen oxide storage catalytic converter and the SCR catalytic converter, and (iii) a position downstream of the SCR catalytic converter (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claim 32, Stanglmaier further discloses that the engine is a motor vehicle propelling engine (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claim 34, Stanglmaier further discloses that wherein a desired ammonia generation quantity which is to be generated during a current regeneration operating phase of the nitrogen oxide storage catalytic converter is determined, and the subsequent regeneration operating phase is carried out as a function of the desired ammonia generation quantity determined (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claims 35 and 42, Stanglmaier further discloses that wherein a condition whereby the recorded exhaust gas air ratio downstream of the nitrogen oxide storage catalytic converter drops below a threshold value, which is predetermined as a function of the desired ammonia generation quantity, is used as a criterion for terminating a respective regeneration

operating phase of the nitrogen oxide storage catalytic converter (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claim 36, Stanglmaier further discloses that wherein a condition whereby the recorded exhaust gas air ratio downstream of the nitrogen oxide storage catalytic converter drops below a threshold value, which is predetermined as a function of the desired ammonia generation quantity, is used as a criterion for terminating a respective regeneration operating phase of the nitrogen oxide storage catalytic converter (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claims 37 and 43, Stanglmaier further discloses that wherein during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claims 38 and 44, Stanglmaier further discloses that wherein during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claim 39, Stanglmaier further discloses that wherein, during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion

Art Unit: 3748

device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Regarding claim 40, Stanglmaier further discloses that wherein, during a respective regeneration operating phase of the nitrogen oxide storage catalytic converter, the combustion device is operated under lean-burn conditions, in particular with an air ratio of between 1.0 and 1.2, and the exhaust gas air ratio upstream of the nitrogen oxide storage catalytic converter is lowered into the rich range (λ < 1) by reducing agent being fed to the exhaust gas (e.g. See Fig. 1; col. 3, lines 49-67; col. 4, lines 1-67; col. 5, lines 1-8).

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 18, and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Twigg'874 in view of Twigg et al. (Twigg) (Patent Number 6,857,265).

Regarding claims 18, and 22, Twigg'874 discloses all the claimed limitation as discussed above except that an second oxidation catalytic converter arranged as last in exhaust gas aftertreatment component, as seen in the direction of flow of the exhaust gas.

Twigg discloses an installation for aftertreatment of exhaust gas (20) generated by an internal combustion engine (10), comprising: a nitrogen oxide storage catalytic converter (28), and at least one of: an NO2 producing catalytic converter, and a particulate filter (26) arranged at one of: (i) a position upstream of the nitrogen oxide storage catalytic converter; an oxidation catalytic converter (24) arranged as a first exhaust gas aftertreatment component, as seen in the direction of flow of the exhaust gas; and an oxidation catalytic converter (30) as a last exhaust gas aftertreatment component as seen in the direction of flow of the exhaust gas (e.g. See Fig. 1; col. 5, lines 49-67; col. 6, lines 1-65).

It would have been obvious to one having ordinary skill in the art at the time the invention was made, to use oxidation catalytic converter arranged as a first and last in the exhaust gas aftertreatment component, as seen in the direction of flow of the exhaust gas of Twigg'874, as taught by Twigg for the purpose of oxidation the NOx in the exhaust gas of an internal combustion engine, so as to reduce the poisoned materials in the exhaust purifying catalyst system and to reduce amount of nitrogen oxides in the exhaust gas of the lean-burn engine, and further improve the performance of the engine and the efficiency of the exhaust purifying catalyst system.

Prior Art

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure and consists of five patents:

Hu et al. (Pat. No. 7063642), Kupe et al. (Pat. No. 6832473), Hu et al. (Pat. No. 7062904), Minami (Pat. No. 6865882), and Deeba (Pat. No. 6912847) all discloses an exhaust gas purification for use with an internal combustion engine.

Application/Control Number: 10/541,311 Page 12

Art Unit: 3748

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner

should be directed to Examiner Binh Tran whose telephone number is (571) 272-4865. The

examiner can normally be reached on Monday-Friday from 8:00 a.m. to 4:00 p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor,

Thomas E. Denion, can be reach on (571) 272-4859. The fax phone numbers for the organization

where this application or proceeding is assigned are (571) 273-8300 for regular communications

and for After Final communications.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

BT

June 26, 2006

Binh Q. Tran

Patent Examiner

Art Unit 3748